

Tanques externos a simple y doble pared

Capacidad nominal	Diámetro externo	Largo de la pared	Largo total (Eslora total)	Distancia entre los soportes	Anchura de los soportes	Boca de acceso	Espesor de las paredes				Número de cáncamos de levantamiento
							Clase A		Clase B		
							S1	S2	S1	S2	
(m ³)	ØDz	Lp	Lo	Fr	Sf	DN	[mm]	[mm]	[mm]	[mm]	[szt]
1	1000	1150	1450	650	150	600	5	3	5	3	2
3	1250	2300	2720	1675	150	600	5	3	5	3	2
5	1250	3900	4320	3275							2
3	1600	1500	2040	700	150	600	5	3	5	3	2
5	1600	2500	3040	1700							2
8	1600	4000	4540	3200							2
10	1600	5000	5540	4200							2
13	1600	6500	7040	5700							2
16	1600	7900	8440	7100							2
10	2000	3000	3660	2000	200	600 o 800	6	4/5	6	4/5	2
13	2000	4000	4660	3000							2
16	2000	5000	5660	4000							2
20	2000	6150	6810	5150							2
25	2000	8000	8660	7000							2
30	2000	9500	10160	8500							2
36	2000	11300	11960	10300							2-4
20	2500	4000	4800	2750	250	600 o 800	6	4/5	7	4/5	2
25	2500	5000	5800	3750							2
30	2500	6000	6800	4750							2
40	2500	8000	8800	6750							2
50	2500	10000	10800	8750							2
60	2500	12000	12800	10750							2
70	2500	14000	14800	12750							2-4
40	2900	6000	6900	4550	300	600 o 800	7	4	9	4	2
50	2900	7500	8400	6050							2
60	2900	9000	9900	7550							2
70	2900	10500	11400	9050							2-4
80	2900	12000	12900	10550							4
100	2900	15000	15900	13550							4
120	3000	17000	17960	15500							4

Ekonstal Sp. z o.o. Sp. K.

Ul. Słoneczna 30
88-230 Piotrków Kujawski - Poland
Tel./fax +48 54 265 49 11

www.ekonstal.pl
ekonstal@ekonstal.pl

Distribuidor exclusivo

Ferrero S.p.A.

Via Pancalieri, 1
12030 Casalgrasso [CN] - Italy
Tel. +39 011 975 777

info@ferrero-industrial.com
www.ferrero-industrial.com